

P-9D series microphone specifications



GENERAL:

The McMARTIN Model P-9D is a versatile, extremely rugged dynamic microphone. It may be held in the hand, mounted on a stand, or hung on a hook when not in use. It features a "voice" response for high intelligibility. It is well suited for dispatch work, public address, and all types of paging work. The case, shaped to fit the hand, is of die cast zinc alloy, satin chrome plated. The P-9D has a push-to-talk switch.

INSTALLATION:

The McMARTIN P-9D is supplied in either low impedance (200 ohms) or high impedance (25,000 ohms). The high impedance P-9D uses a one conductor shielded cable with an Amphenol MC1M screw on type connector. The low impedance P-9D uses a two conductor shielded cable with an Amphenol MC2M screw on type connector and is suitable for installations using long lengths of balanced line cable.

SPECIFICATIONS:

Type: Pressure operated dynamic.

Frequency Response: 150-7000 c.p.s.

Sensitivity: 52 db below 1 volt/dyne/sq. cm., open circuit, at high impedance.

Polar Pattern: Essentially omni-directional.

Impedance: 200 ohms or hi impedance (25,000 ohms)

Mounting: Standard $\frac{5}{8}$ " - 27 thread.

Finish: Satin Chrome.

Dimensions: $4\frac{7}{8}$ " x $2\frac{21}{32}$ " x $2\frac{5}{32}$ " overall.

Weight: 20 oz., less cable.

Cable: 7 feet.

GUARANTEE:

All McMARTIN microphones are individually and thoroughly tested before leaving the factory and are guaranteed against defective materials and workmanship for one year, providing that instructions are fully complied with and that units are not opened or tampered with in any way.

McMartin

McMARTIN INDUSTRIES, INC.
Omaha, Nebraska, U.S.A.